

CNC MACHINE TOOL CO.

FMC 6026

CNC VERTICAL MACHINING CENTER with FREEDOM M CNC CONTROLLER



YOU NOW HAVE A CHOICE WITH FREEDOM.

STANDARD FEATURES

- COOLANT THRU PREPPED
- DUAL LED WORKLIGHTS
- 15 IN. TOUCH SCREEN COLOR MONITOR
- 4TH AXIS PREWIRE
- 3,000 BLOCK/SEC EXECUTION
- HIGH SPEED HIGH PRECISION SOFTWARE
- CROSS ROLLER BEARING WAY

- 12,000 RPM A/O SPINDLE
- DUAL CONTACT SPINDLE NOSE
- 70MM CERAMIC SPINDLE BEARINGS
- 37.5 PEAK HORSEPOWER
- 30 POSITION DUAL ARM TOOL CHANGER
- CHIP AUGER

MACHINE CONFORMS TO UL-508A CERTIFICATION PER SGS PERMIT # SGSNA/19/TW/00028.

FMC 6026

CNC VERTICAL MACHINING CENTER with FREEDOM M CNC CONTROLLER

Specifications

TRAVEL	
X-axis Travel (in.)	60 in.
Y-axis Travel (in.)	25.5 in.
Z-axis Travel (in.)	25 in.
Spindle nose to table (in.)	4-28 in.
Spindle center to column (in.)	30 in.
TABLE	
Table Dimensions (in.)	63 x 25.5 in.
T-Slot Dimensions (in.)	(5) 3.75 x .709 x 3.9 in.
Max. Table Load (lbs.)	2,200 lbs.
SPINDLE	
Spindle Type	Cat-40/BT-40*
Spindle Speed (RPM)	12,000/15,000* RPM
Spindle Motor (HP) Peak	37.5 HP
ACCURACY	
Positioning accuracy	0.00015/12 in.
Repeatability accuracy	0.0001/12 in.
FEED	
Rapid Traverse Rate X, Y, & Z (IPM)	1,410 IPM
Cutting Feedrate (single axis moves up to)	790 IPM MAX.
Ballscrew Diameter X, Y, & Z Axis (mm)	45 mm
Axis Drive Motor X, Y & Z (HP)	3.9, 3.9, 5.2 HP
ATC	
Tool Capacity	30/40*
Tool Change Type	Dual Arm
Tool Change Time (sec.)	1.9 sec. tool to tool
Max. Tool Weight (lbs.)	15 lbs.
Max. Tool Diameter (in.) (with adjacent tool)	4.9 (3.1) in.
Max. Tool Length (in.)	11.8 in.
Tool Selection Method	Random
OTHER	
Machine Dimensions D x W x H (in.)	90.5 x 183 x 112.6 in.
with Chip Conveyor	CONTACT DEALER
Machine Weight (lbs.)	17,600 lbs.
All specifications are subject to change without notice.	/ Optional

5th Axis Servo Disconnect (Simultaneous) 5th Axis Servo Disconnect (4 + 1) 5-Axis Vector Software 15K Air/Oil Spindle FR-5C Rotary Table - Pneumatic (Req. 4th Axis Disconnect) FR-5C Rotary Table - Manual (Req. 4th Axis Disconnect) FR-6 Rotary Table (Reg. 4th Axis Disconnect) FR-8 Rotary Table (Req. 4th Axis Disconnect) FTR-8 Tilt Rotary (Req. 4th/5th Axis Disconnect) FR-10 Rotary Table (Req. 4th Axis Disconnect) FR-5C Tailstock FR-8 Tailstock FR-10 Tailstock **Manual 5C Collet Closure** 40 Tool Dual Arm Tool Changer 6 Inch 3-Jaw Chuck w/ Adapter 8 inch 3-Jaw Chuck w/ Adapter 10 inch 3-Jaw Chuck w/ Adapter Marposs Hard Wired Tool Presetter **Marposs Wireless Tool Presetter Marposs Wireless Spindle Probe Marposs Wireless Probe & Tool Presetter** Renishaw CAT40 Wireless Spindle Probe w/ Software Renishaw BT40 Wireless Spindle Probe w/ Software Renishaw Hard Wired Tool Presetter w/ Software Renishaw CAT40 Wireless Probe & Tool Presetter w/ Software Renishaw BT40 Wireless Probe & Tool Presetter w/ Software

Chain Type Chip Conveyor Automatic Pallet Changer

Extended Z Travel & Column 10 IN.

Coolant Thru 500 PSI System

4th Axis Servo Disconnect

Rear Washdown Kit

FEATURES

FREEDOM M CNC CONTROLLER

Highlighted Features

4 GB Memory 3000 Blocks/Sec 3000 Block Buffer Memory 15-Inch Touch Screen Monitor

See Freedom M CNC Controller Brochure for all features and more information!



Authorized Freedom Dealer



CNC MACHINE TOOL CO.

WWW.AASALESANDSERVICE.COM
1200 N VAN BUREN ST, STE D
ANAHEIM, CA 92807